

LED STREET LIGHT G2 - 75W



PHILIPS
LED Driver



Product Specification

Module	: 2
Part No.	: AvL-SL-75W-P01-yK G2
Lumen (lm)	: 9000
Efficiency (lm/W)	: 120
Power (W)	: 75
Colour Temperature, CCT (K)	: 3000K/4000K
Colour Index (CRI)	: ≥ 70
Beam Angle ($^{\circ}$)	: Asymmetrical
Weight (Kg)	: 8
Dimmable	: No
Spigot Opening (Pole)(mm)	: ≥ 54
Depth	: 100

General Specification

Input Voltage (V_{AC})	: 220 - 240
Power Factor (PF)	: ≥ 0.9
THD (%)	: ≤ 20
IP Rating	: IP 65
Materials	: Die-Cast Aluminium
Driver	: External LED Driver (Within Casing)
Life Time (hours)	: 50,000
Warranty (years)	: 5
Finishing Color	: Silver
Operating Temp. ($^{\circ}C$)	: $-20^{\circ}C \sim 50^{\circ}C$
Working Humidity (% RH)	: 10 ~ 90
Storage Temp. ($^{\circ}C$)	: $10^{\circ}C - 65^{\circ}C$

Remark:

Application: Outdoor Application | Street Lighting | Compound Lighting | Walkway Lighting

*y refers to CCT: 3-3000K, 4-4000K



ISO 9001
BUREAU VERITAS
Certification



Malaysian Brand


MADE IN MALAYSIA

AdvanLED


LED STREET LIGHT G2 - 75W

AdvanLED

Photometric Result :




Dimension (mm) :




	75W
Length (L1)	554
Length (L2)	320
Height (H)	130

Connection Diagram (mm) :



Live (Brown)
Neutral (Neutral)
Earth (Green Yellow)



AdvanLED

